



**TAUBLOCK HTB03, HTB06**  
***TOW ROPE BLOCK HTL06R, HTB06***



# TAUBLOKK HTB03, HTB06 TOW ROPE BLOCK HTB03, HTB06

Taublokkene er konstruert for snurrevad opp til ca 30-50 fot. Blokkene henges i galge eller davit akterut for innhaling av tauene fra sjøen, slik at ledeblokker blir overflødig.

Snurrevad-tauene kveiles direkte på dekk eller bingje, slik at en kan sette uten å forstyrre annet arbeid på fordekket.

Standard leveranse omfatter manøverventil og 4 m slanger. Det er benyttet sjøvannsbestandig materialer i alle utsatte deler.

The tow rope block is designed for seine fishing in a depth of 30-50 feet. The rope blocks hung from gallows or a davit aft for hauling the ropes. The guiding blocks will not be necessary.

The Seine ropes coiled directly on deck or bin., ready for the next setting without disturbing other work on the front deck.

The block is made of sea water resistant materials.

Standard delivery includes control valve and 4 mtrs hoses.

TABELL 1 NORSK

TAUBLOKK	HTB03	HTB06
Trekraft Ø130-270	200-415 kg	
Trekraft Ø250-380		500-800 kg
Turtall	94 o/min	115 o/min
Hivehastighet Ø130	200 m/min	
Hivehastighet Ø240	800 m/min	
Hivehastighet Ø270		415 m/min
Hivehastighet Ø380		500 m/min
Oljemengde	60 l/min	115 l/min
Oljetrykk	80 bar	140 bar
Vekt		

TABEL 1 ENGLISH

TOW ROPE BLOCK	HTB03	HTB06
Pull Ø130-270	200-415 kg	
Kgs Ø250-380		500-800 kg
Speed	94 rpm	115 rpm
Hauling speed Ø200	200 m/min	
Hauling speed Ø200	800 m/min	
Hauling speed Ø200		415 m/min
Hauling speed Ø200		500 m/min
Oil flow	60 lit/min	115 lit/min
Oilpressure	80 bar	140 bar
Weight		

