



REKKERULL HR03
RAIL ROLLER HR03



REKKERULL HR03

RAIL ROLLER HR03

REKKERULL TYPE HR03 leveres i to standard lengder. Skjoldene er av sjøvannsbestandig aluminium og rekkefeste av varmgalvanisert stål. Den gummierte rullen drives av en hydraulisk motor og bringer garn og fisk letteres fram til garnspillet. Skader på garn vil dermed reduseres. Nylonruller i begge skjold reduserer slitasje og friksjon. Standard leveranse omfatter manøverventil og 4 meter slanger.

RAIL ROLLER TYPE HR03 is available with roller in two standard dimensions. Side shields are made of sea water resistant aluminium and rail bracket of warm galvanized steel. A hydraulic motor operates the rubberized roller, that will cause less damage to the net than conventional rollers. Plastic rollers in the shields reduce the friction. Standard delivery includes control valve and 4 mtrs hoses.

TABELL 1 NORSK

REKKERULL	HR03
Trekkraft	230 kp
Turtall	64 o/min
Hivehastighet	50 m/min
Oljemengde	22 l/min
Oljetrykk	70 kp/cm ²
Vekt	100 kg

TABEL 1 ENGLISH

RAIL ROLLER	HR03
Pull	230 kg
Speed	64 rpm
Hauling speed	50 m/min
Oil flow	22 lit/min
Oil pressure	70 kp/cm ²
Weight	100 kg

