



Sløyekar HSK

Fish hopper HSK



SLØYEKAR HSK 151211

Sløyekaret er produsert i sjøvannsbestandig aluminium og rustfritt stål.

Karbunnene heises opp og ned med en hydraulisk sylinder plassert midt i karet. Styrepanelet er plassert på langsiden.

For sløying av fisk er karet utstyrt med en plastkant.

Åpningene på langsiden og midtsiden er utstyrt luker som enkelt kan åpnes opp for flytting av fangst mellom rommene i karet.

Åpningene ved bunnplaten låses med en eksentrisk lås som gjør karet så tett som mulig.

Karet leveres med løftebolter.

FISH HOPPER HSK151211

The Fish Hopper is made of sea water resistant aluminium and stainless steel.

The tilting floors are controlled by hydraulic cylinders that are placed in the centre of the hopper, with controls mounted externally on the hopper. For gutting, the fish hopper is supplied with a plastic edge.

By opening the vertical hatches on the outer edge and in the centre, it becomes very easy to move the catch between the fish chambers.

The doors on each side at the bottom of the fish hopper are kept closed by an eccentric locker which keeps the fish hopper as water tight as possible.

The delivery includes lifting bolts.

Sløyekar

HSK151211

Fish hopper HSK151211

Oljemengde

12 l/min

Oil flow

12 lit/min

Oljetrykk

140 kp/cm²

Oil pressure

140 kp/cm²

Vekt

250 kg

Weight

250 kgs



